

**Amendments to the Claims:**

1. (currently amended) A hand held oral irrigation device for irrigating an oral cavity with a fluid ~~having a tip for dispensing fluids, the device~~ comprising:  
a reservoir for storing the fluid; ~~fluids; and~~  
a body; and  
an elongated nozzle,  
wherein the reservoir defines ~~body and the reservoir define~~ a first major diameter at a lower end of the oral irrigation device and the body and reservoir combine to define a second major diameter at an upper end of the oral irrigation device, the first major diameter being larger than the second major diameter.
2. (currently amended) The device of claim 1, wherein the body further comprises a motor, a pump, and a drive mechanism coupling the motor to the pump, said pump for controllably delivering the fluid ~~the fluids~~ from the reservoir to the nozzle ~~the tip~~.
3. (currently amended) The device of claim 2, further comprising:  
a three-way control structure having a first button for activating the motor, a second button for de-activating the motor, and a third button for releasing the nozzle ~~the tip~~ from the body.
4. (original) The device of claim 2, wherein the drive mechanism includes a pump gear coupled with said motor, wherein the pump gear includes an eccentric offset disc extending from said pump gear.
5. (original) The device of claim 4, wherein the drive mechanism further comprises:  
a connecting rod coupled with the eccentric offset disc.
6. (original) The device of claim 5, wherein the connecting rod further comprises:  
a hollow cylindrical portion receiving the eccentric offset disc of the pump gear;  
an arm extending from the cylindrical portion; and  
a ball end positioned at the end of said arm.
7. (currently amended) The device of ~~claim 2~~ claim 6, wherein the pump includes:  
a pump head having an inlet fluid port, an outlet fluid port, and an interior fluid channel in fluid communications with said inlet and outlet fluid ports;

a pump body defining a cylindrical chamber in fluid communications with said interior fluid channel of said pump head; and  
a piston having a bottom portion and a top portion, the bottom portion receiving at one end the ball end of the connecting rod, said piston positioned within said cylindrical chamber of the pump body;  
wherein the inlet fluid port is fluidly coupled with the reservoir, and the outlet fluid port is fluidly coupled with the tip.

8. (original) The device of claim 7, wherein the top portion of the piston includes:  
an annular flange;  
an interior pedestal; and  
an annular recess defined between the annular flange and the interior pedestal.
9. (original) The device of claim 7, wherein the pump further comprises:  
an inlet fluid valve regulating fluid flow into said inlet fluid port; and  
an outlet fluid valve regulating fluid flow into said outlet fluid port.
10. (original) The device of claim 9, wherein when the piston is moved downwardly within the cylindrical chamber of the pump body, the inlet fluid valve is open, the outlet fluid valve is closed, and fluid is drawn from the inlet port into the cylindrical chamber of the pump body.
11. (original) The device of claim 9, wherein when the piston is moved upwardly within the cylindrical chamber of the pump body, the inlet fluid valve is closed, the outlet fluid valve is open, and fluid is expelled from the cylindrical chamber of the pump body to the outlet fluid valve for delivery to the tip.
12. (original) The device of claim 9, wherein the inlet fluid valve includes a first reed valve made of flexible fabric material.
13. (original) The device of claim 9, wherein the outlet fluid valve includes a second reed valve made of flexible fabric material.
14. (original) The device of claim 10, wherein the first reed valve includes:  
a rim defined on a portion of a perimeter of the first reed valve;  
a hinge portion; and

a flap portion interior to the rim, a first end of said flap portion attached to the hinge portion, said flap positioned relative to the rim so as to define a crescent shaped opening.

15. (currently amended) The device of ~~claim 12~~ claim 14, wherein the flap portion has a diameter, and wherein the interior fluid channel of the pump head has a diameter, the diameter of the flap portion being larger than the diameter of the interior fluid channel.

16. (original) The device of claim 1, wherein the reservoir is detachable from the body.

17. (original) The device of claim 1, wherein the reservoir has a top portion and a bottom portion, the top portion having a first cross section, the bottom portion having a second cross section, the second cross section being larger than the first cross section.

18. (original) The device of claim 1, wherein the reservoir further comprises:  
an opening positioned at a top end; and  
a lid releasably secured about said opening.

19. (original) The device of claim 7, wherein the body further comprises:  
an inlet conduit fluidly coupling said reservoir with said inlet fluid port; and  
an outlet conduit fluidly coupling said outlet fluid port with said tip.

20. (original) The device of claim 7, wherein the body further comprises an inlet conduit fluidly coupling said reservoir with said inlet fluid port; and wherein the reservoir further comprises a fluid access valve fluidly coupling with said inlet conduit.

21. (original) The device of claim 20, wherein the reservoir further comprises:  
a shelf portion defined about a bottom portion of the reservoir; and  
a base at the bottom end of the reservoir; and  
wherein the fluid access valve further comprises:  
a channel defined within the reservoir extending from the shelf to the base,  
said channel receiving said inlet conduit;  
a seal positioned about the top end of the channel;  
a spring extending upwardly from the base within the reservoir;  
a ball positioned within the channel between said seal and said spring; and

a reservoir inlet conduit positioned along the base of the reservoir, the reservoir inlet conduit fluidly coupled with the channel, so that fluid is drawn from the bottom of the reservoir.

22. (original) The device of claim 9, wherein the inlet fluid valve of the pump is vertically positioned within the body at a location lower than a full level of fluid in the reservoir, thereby self priming the pump with said fluid.

23. (currently amended) The device of claim 1, wherein the nozzle ~~the tip~~ further comprises an annular groove; and wherein the body further comprises:

a nozzle holding tip ~~tip holding~~ structure having a cylindrical wall defining a cylindrical opening;

a slot defined within said cylindrical wall;

a clip having an interior lip, said interior lip positioned within said slot and extending into said cylindrical opening; and

a spring for biasing the lip of the clip into the slot;

wherein when the spring is uncompressed, the lip is received within the annular groove of the nozzle ~~the tip~~ to secure the nozzle ~~the tip~~ to the body.

24. (original) The device of claim 1, wherein the reservoir has a capacity of approximately 120 to 200 ml of fluid.

25. (original) The device of claim 2, wherein the body includes a wall structure defining a first and second section within the body, the first section containing the pump, and the second section contains the motor and the drive mechanism, wherein the first and second sections are fluidly isolated.

26. (currently amended) A hand held oral irrigation device for irrigating an oral cavity with a fluid ~~having a tip for dispensing fluids~~, the device comprising:

a reservoir for storing the fluid; ~~fluids~~; and

an elongated nozzle; and

a body including a pump for pumping the fluid ~~fluids~~ from the reservoir to the nozzle ~~the tip~~, wherein said pump includes an inlet valve and an outlet valve, the inlet valve including a reed valve made of flexible fabric material.

27. (original) The device of claim 26, wherein the outlet valve includes a reed valve made of flexible fabric material.
28. (original) The device of claim 26, wherein the reed valve includes:  
a rim defined on a portion of a perimeter of the reed valve;  
a hinge portion; and  
a flap portion interior to the rim, a first end of said flap portion attached to the hinge portion, said flap positioned relative to the rim so as to define an opening.
29. (new) A hand held oral irrigation device for irrigating an oral cavity with a fluid, the device comprising:  
a body including a top end, a bottom end and housing a pump for pumping the fluid;  
an elongated nozzle coupled to the top end of the body; and  
a fluid reservoir coupled to the bottom end of the body,  
wherein the device has a first diameter defined by the reservoir and a second diameter extending across the body, wherein the first diameter is below the second diameter on the device and greater than the second diameter.
30. (new) The device of claim 29, wherein the nozzle is detachably coupled to the top end of the body.
31. (new) The device of claim 29, wherein the reservoir is detachably coupled to the bottom end of the body.
32. (new) The device of claim 29, wherein the reservoir and body combine to form a gripping surface.
33. (new) The device of claim 29, further comprising a third diameter extending across the body, located between the first and second diameters and exceeding the second diameter.
34. (new) The device of claim 33, further comprising a control element for starting or stopping the pump, wherein the control element is located in the area of the second diameter.